

PRODUCT DESCRIPTION		PRODUCT PROPERTIES												
		Shore A Hardness ±5	Operating Temp °C Min. Max.	Application Temp °C Min. Max.	Tensile Strength Mpa (ISO 8339)/(ISO37)	Shear Strength Mpa (ASTMD 1002)	Paintable (Tests are recommended)	Colours Available	Elongation at Break (%) (ASTMD 1002)	Skin Time (Minutes) (23°C & 50% R.H)	Cure Rate (mm per 24hrs) (23°C & 50% R.H)	Dynamic Movement (%)	Package Size (mL)	Part number: Fix (Product Number) (Product Difference) (Colour) (Package in Litres: eg 300mL = L03 or 600mL = L06
FIX8 Synthetic Adhesive Silicone FIX8 FN Finishing Adhesive Silicone FIX8 HT - MOQ APPLIES High Track Adhesive Silicone	40	-40 +100	5 to 30	1.00	1.00	NO	BK, WH, AW	> 300	40	3	25	300 Cart	FIX8_ _ _ _	
	35	-40 +100	5 to 30	1.00	1.00	NO	ALL, TRANS	> 100	10	3	12.5	300 Cart	FIX8FN_ _03	
	50	-40 +100	5 to 30	1.00	1.80	NO	BK, WH	> 80	20	4	12.5	300 Cart 600 Foil	FIX8HT_ _ _ _	
	48	-40 +100	5 to 30	2.20	1.60	YES	BK, WH, GY	> 300	15	3	25	290 Cart 600 Foil	FIX15_ _ _ _	
FIX190 High Strength Adhesive Sealant	45	-40 +100	5 to 30	3.60	1.60	YES	BK, WH	> 230	45	3	20	600 Foil	FIX190_ _ _ _	
FIX190FWT High Strength Adhesive Sealant	45	-40 +100	5 to 30	3.60	1.60	YES	BK, WH	> 230	12	4	20	290 Cart 600 Foil	FIX190FWT_ _ _ _	
FIX200 POLYMER & GLASS Flexible Adhesive Silicone	25	-40 +100	5 to 30	0.75	0.75	NO	BK	600	30	1	50	310 Cart	FIX200BK L03	
FIXCLEAR 100% Clear Adhesive Sealant	40	-40 +100	5 to 30	1.00	1.00	YES	Clear	> 230	12	4	20	290 Cart	FIXClear L03	

FIX8AL and FIX8TP have 12 minute working time.

RECOMMENDED APPLICATIONS															
PRODUCT DESCRIPTION	Above & Below Waterline	Glazing Fixing & Finishing	Structural Fixing & Finishing	UV Stable Non-Yellowing White	All Metals, Fiberglass	Aluminium & Stainless Steel	*Polymer Window	External Exposed Wipes	All Timber Types May Require Primer	Deck Gear & Fitting Seals	Deck to Hull Cabin Tops etc.	Teak Deck Caulking	Teak Deck Adhesion	Synthetic Deck Adhesion	100% Fuel & Solvent Resistant
FIX8, FIX8 FN, FIX8 HT Structural Silicone RTV-1 Bonding & Finishing. (Anti-mould)		✓	✓	✓	✓	✓		✓	✓	✓					
FIX15 Multipurpose Exterior /Interior Bonding & Sealing	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓				
FIX190 Structural Exterior / Interior & Glass Bonding & Sealing	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓				
FIX200 POLYMER & GLASS Polymer Window Silicone		✓		✓	✓	✓	✓ *	✓	✓						
FIXCLEAR 100% Clear Multipurpose Adhesive Sealant	✓	✓	✓		✓	✓			✓						
FMP100 & FMP200 FIXIT Structural Rigid Timber & Foam Core Bonding	✓		✓		✓ ***				✓						
FIX3 Synthetic Flooring Bonding Adhesive			✓	✓	✓	✓		✓	✓	✓				✓	
FIX30 Universal Construction, Floor & Tile Adhesive Sealant			✓		✓	✓		✓	✓				✓		
FIX1 DC TEAK DECK CAULKING Improved Chemical Cleaner Resistance Teak and Cork Deck Caulking				✓	✓	✓		✓	✓			✓			
FM30 FUEL MASTER PAC240 Specialist Fuel Tank Adhesive Sealant	✓		✓		✓	✓									✓
MP101 Extra Fine White 2K Filler	✓ **				✓	✓		✓	✓						
FIXSEAL FIX1060 i.i PENETRATING Timber & Porous Substrate Epoxy Sealer	✓								✓			✓			
FIX 2 Multipurpose Adhesive Sealant	✓			✓	✓	✓			✓						

* Polymer window means window made from acrylic or polycarbonate
** MP101 must be coated with marine paint for below waterline application
*** One component must be porous such as timber or structural foam core
**** Etch prime aluminium before bonding

SUPERIOR BONDING PRODUCTS

Technical Assistance:

Fixtech Pty Ltd,
Unit 1, 20 Export Drive, Molendinar, QLD 4214,
P.O. Box 568, Southport, QLD 4215 AUSTRALIA
Ph: +61 (7) 5530 1099 (Overseas)
Ph: 1300 887 077 (Australia wide)
Email: info@fixtech.com.au

Fixtech LLC
8951 Cypress Waters Blvd, Suite 160,
Dallas, TX 75019
Ph: +1 954 900 2916 MP: +1 713 2657 077
Email: sales@fixtechus.com
Web: www.fixtechus.com

Fixtech International Limited, Taiwan Branch
96 hongping Road, Saogang, Kaohsiung City, 812 TAIWAN
Ph: +886 (7) 8062506 Fx: +886 (7) 8062811
Email: info@fixtech.asia

Fixtech International Limited, Zhuhai (Southern & Central China)
3rd F, Building 8, No.1 Pingdong Road, Nanping Technology Park,
Zhuhai City 519060, Guangdong, CHINA
Ph: +86 756 7750077 Fx: +86 756 8513101
Email: sales@fixtech.com.cn

As a general guideline, to achieve successful adhesion, abrade and clean with Industrial Alcohol and ensure that the surface is dry and clean before adhering with Fixtech products. For further details, including TDS, MSDS and application hints and tips, please refer to our website: www.fixtech.com.au

*** Full property strength achieved after 7 days. Full property strength achieved after 9 hours. Full property strength achieved after 9 hours. Full property strength achieved after 9 hours.

FIX1060 i.i Epoxy Solvent Based Sealer	750ml, 500ml, 1kg	a/u	initial 09	30	a/u	Amber	YES	a/u	a/u	35 to 5	+0+	a/u		
MP101 Extra Fine White 2K Filler	1kg inc Activator	a/u	30	5	a/u	White	YES	a/u	a/u	25 to 5	+0-	8L		
FAC240PSL05 US Approved Fuel Resistant	5kg	20	2 pack 2 Hr	90	200	DK Grey	YES	2.0	2.0	35 to 5	+0-	09		
FIXDC Cork, Teak, Synthetic Decking	300 Cart	52	3	30	330	BK GY	ON	0.1	0.1	30 to 5	+0-	2L		
FIX30WHL09 Universal Floor & Tile Bonding Adhesive Sealant	1009 foil	02	5.1	07	000	HM	SEA	5.7	0.1	30 to 5	+0-	a/u		
FIX3FBTKL09 Synthetic Decking Bedding Adhesive	1009 foil	52	3	07	052	Teak	ON	0.01	0.01	30 to 5	+0-	07		
FMP200 Liquid 100% Waterproof Adhesive	750 Bottle	a/u	2hr initial	30	a/u	Transp	YES	0.021	0.021	53 to 5	+0-	a/u		
FMP100 Gel 100% Waterproof Adhesive	310 Cart	a/u	2hr initial	30	a/u	Transp	YES	0.021	0.021	53 to 5	+0-	a/u		

FIX 8

300mL

Structural Adhesive Silicone

(Available: White, Antique White, Black)

- Structural bonding of most substrates
- Suitable for marine exposure
- Above waterline bonding including synthetic decking
- Can be used for under waterline screw fitting seals
- Medium modulus stays flexible
- Weatherproof and U.V. resistant
- Cannot be stained or painted over
- 600ml MOQ applies



FIX8FN

300mL

Expert Finishing Silicone

(Available: Aluminium and Translucent with anti mould)

- Smooth to apply and bonds to most substrates
- Suitable for above waterline marine exposure
- Weatherproof and U.V. resistant
- Suitable for acid rain zones
- Excellent smooth shiny finishing
- Medium modulus stays flexible
- Cannot be stained or painted over



FIX8HT

300mL

Structural Silicone RTV-1

Thixotropic structural bonding

(Available: White & Black with anti mould.)

- Structural bonding of most substrates
- Good green strength to hold before cure
- Suitable for marine exposure
- Suitable panel and direct glass bonding
- Above waterline bonding and interior bonding
- Can be used for under waterline screw fitting seals
- High modulus and high shore A hardness
- Weatherproof and U.V. resistant
- Cannot be stained or painted over
- 600ml MOQ applies



FIX15

290mL
600mL

Multipurpose Exterior /Interior Bonding & Sealing

(Available: Black, White, Grey)

- All fittings, fixtures and fasteners
- UV stable, age resistant & weatherproof
- Thru hull fittings
- Primerless adhesion to many surfaces
- No bubbles for perfect finish
- Waterproof sealing and wipes
- Saves time and costs
- Paintable when wet and flow coat after 2 hours
- Bond above and below water



FIX190, FIX 190FWT

290mL
600mL

Structural Exterior / Interior & Glass Bonding & Sealing

(Available: White and Black. Std & Fast)

- Primerless adhesion to many surfaces
- Bonding to all structural foam core materials
- Structural bonding Fly-bridge & Deck to Hull
- UV Stable, age resistant and weatherproof
- Direct glazing bonding & sealing
- Bonding components, panels etc. (PP blend fiberglass & aluminium)
- Drinking water safe
- Waterproof sealing and wipes
- Excellent impact resistance
- Thru hull fittings
- Bond above and below water



FIX200

310mL

Polymer Window Silicone

(Available: Black)

- Ideal for Acrylic, Polycarbonate and Glass profiles
- Structural bonding & sealing
- Primerless adhesion to many surfaces
- UV stable, age resistant and weatherproof



FIXCLEAR

290mL

100% Clear Multipurpose Adhesive Sealant

- Mirrors, veneer panels, LED and optic fibre lighting
- Insulation and internal bonding
- 100% waterproof



FM30 FUEL MASTER FAC240

500mL

Specialist Fuel Tank Adhesive Sealant

- Thru tank fittings
- Internal baffle bonding
- Lids and inspection hatch bonding
- 5m head pressure tested



MP101 EXTRA FINE WHITE 2K FILLER

1 Kg

(Available: White with Red activator)

- 2 pack ultra smooth finishing filler
- Quick to cure and 30 minute sandable
- Ideal for fiberglass, timber, steel and aluminum
- Paintable
- Must be sealed for application below waterline



FIX3

600mL

Synthetic Flooring Bonding Adhesive

(Available: Teak)

- Bonding Flexiteek, Composite PVC, Cork deck etc.
- Primerless adhesion to many surfaces
- Suitable working time, excellent bonding performance.
- Good flexibility
- Excellent shock and sound absorption
- Waterproof, weatherproof, UV stable
- MOQ applies



FIX30

600mL

Universal Construction, Floor & Tile Bonding Adhesive Sealant

(Available: White)

- Bonding Teak Deck, Stone & Ceramic Tiles
- Primerless adhesion to many surfaces
- Good working time, fast strength build-up
- Walk on in 12 hours, no bubble formation
- Age resistant and waterproof
- Excellent shock and sound absorbance
- No fasteners required



FIX1DC DECK CAULKING

300mL
600mL

Improved Chemical Cleaner Resistance Teak and Cork Deck Caulking

(Available: Black, Slate Grey)

- UV Stable, heat, age resistant, waterproof and weatherproof
- Excellent resistance to soap cleaning
- Elastic and does not go hard or brittle
- Easy to apply and sand for a great finish
- No bubble formation
- Not paintable
- Slate Grey available in 600ml only



TEAK CLEANER

5 Ltr

Teak Deck Beautification System

- 1 part Teak cleaner and conditioner system
- Not harmful and 100% biodegradable
- Retain's the teak natural oils and no damage to caulking



FMP100 & FMP200 FIXIT

750gm
310 mL

Structural Rigid Timber & Foam Core Bonding

(Available: Transparent Paste and Honey Liquid)

- End grain bonding
- Strong as epoxy
- One component only
- Clamping required for 1-2 hours only
- Fast turn-around time
- All foam core bonding
- One component must be porous
- Invisible timber joint
- 100% waterproof also bond wet on wet



PR20 PLASTIC PRIMER

1 Ltr

(Available: Clear)

- Polypropylene Plastic surface bonding primer



FIXSEAL FIX1060

Kit sizes:
500ml, 2L, 8L, 40L

Timber & Porous Substrate Epoxy Sealer

Type: Solvent

Colour: Transparent Yellow Tint

- 1:1 mixing ratio, leave for 30 min before applying
- Penetrating to porous substrates
- Suitable for teak deck caulking pre-sealing
- 12 hour open time
- 100% waterproof after cure



FIX 2

125ml

Multipurpose Adhesive Sealant

- Good bond strength on a wide variety of substrates
- Non yellowing white
- High performance mechanical properties
- Flexible elastic rubber when fully cured; movement accommodation up to 20%
- No bubble formation within the sealant
- Primerless adhesion to most common substrates (Compatibility tests recommended)
- Easy to tool and finish
- Excellent extrudability and UV resistance
- Can be painted with all water based paints and many other systems* (Compatibility tests recommended)



APPLICATION TOOLS

FG4

Heavy Duty Caulking tool for cartridges 150mL to 310mL



FG5

Pneumatic Caulking tool for cartridges 290mL to 310mL with pressure regulator.



FG7

Manual heavy duty caulking tool for sausages up to 600ml.



FG8

Pneumatic Caulking tool for sausages up to 600mL, with pressure regulator.



FG111

1:1 ratio, side by side tool for up to 400mL cartridges.



Refer to TDS for more information

Not all products are available at all offices, please contact your local Fixtech office for details.